



The Gorman-Rupp Company

GHS Series (G Series)

The GHS Series of iron, high capacity pumps is designed for continuous duty service for applications in the operating ranges noted. The units are ideal for bulk handling both thin and viscous liquids. For temperature control, backhead and housing jackets are standard; head jackets are available. Also available are carbon graphite bushings for low viscosity liquids, silicon carbide bushings for wear resistance, and numerous seal options. This heavy duty series provides superior rotor shaft support and an integral, maintenance-free radial/thrust bearing, for reduced deflection and wear.



Specifications

Size:	1" (25 mm), 1-1/2" (37.5 mm), 2" (50 mm), 3" (75 mm), 4" (100 mm)
Max Capacity:	600 GPM (38 lps)
Max Viscosity:	2,000,000 SSU (431,000 cST)
Max Pressure:	300 PSI (21 BAR)
Min Temperature:	-60 F (-51 C)
Max Temperature:	675 F (357 C)
Materials of Construction:	Cast Iron, Cast Steel, Stainless Steel

Specifications are subject to change. Please contact your Gorman-Rupp Distributor for more details.



The Gorman-Rupp Company
P.O. Box 1217
Mansfield, Ohio 44901-1217
Tel: 419-755-1011
Fax: 419-755-1251
E-mail: grsales@gormanrupp.com

The Gorman-Rupp International Company
P.O. Box 1217
Mansfield, Ohio 44901-1217
Tel: 419-755-1011
Fax: 419-755-1266
E-mail: intsales@gormanrupp.com

Gorman-Rupp of Canada, Ltd.
70 Burwell Road
St. Thomas, Ontario N5P 3R7,
Canada
Tel: 519-631-2870
Fax: 519-631-4624
E-mail: grcanada@grcanada.com



www.GRpumps.com

©2005-2006 The Gorman-Rupp Company. All Rights Reserved.